

ULUF SERIES

- Single compressor
- Low energy consumption
- Low noise level
- Low heat dissipation
- Insulated inner doors
- Door key lock
- Ergonomic loading
- Heated door frame
- 100% HCFC/CFC free

ALL STANDARD FEATURES

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Prepared for GSM alarm
- Prepared for connection of 2 additional probes
- Auto cycle in case of probe failure
- Ambient temperature display
- Direct download of logged data on USB memory stick
- Direct upload of new software via USB memory stick
- 3-level password protected
- Battery level indication
- Display text available in different languages
- Temperature graph
- Integrated data logger
- RS485/RS232 interface
- Integrated memory for 20 years
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Shows all alarms

MODEL	ULUF 120
Item code	DAI 1395
Dimensions exterior WxDxH (mm)	950x725x810
Capacity (L)	94
Temperature range (°C)	-40 / -20
Power supply (V)	230
Frequency (Hz)	50/60

ULUF 120

The ULUF -40°C range are products of our passion, striving after excellence when we offer the best in low temperature freezing. Once again, we set new standards with the most user friendly controller in the market. All features such as alarms and data logging functions are always included as standard. The Arctiko ULUF -40°C range offers the highest temperature stability world wide!

- 40 °C



Battery backup - 72 hours

Integrated data logger with memory

RS485/RS232 interface

On/off protection

ARCTIKO
The art of simplicity®

Technical specifications

Item code	DAI 1395
Dimensions exterior WxDxH (mm)	950x725x810
Capacity (L)	94
Dimensions interior WxDxH (mm)	360x493x530
Insulation (mm)	120
Temperature range (°C)	-40 / -20
Max. ambient temperature (°C)	25
Power supply (V)	230
Frequency (Hz)	50/60
Power consumption (KWH/24H)	7,4
Current (A)	3,2
Weight (KG)	105
Shipping weight (KG)	135
Shipping weight with wooden packaging (KG)	-
Shipping dimensions WxDxH (mm)	1100x820x1020
Shipping dimensions with wooden packaging WxDxH (mm)	-
No. of compressors	1
Visual / acoustic alarm	Yes
Power failure alarm	Yes
Adjustable high/low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Alarm display as text - not codes	Yes
Contact for remote alarm	Yes
Prepared for GSM alarm module	Yes
Approx. hrs of battery back up for alarms and temperature display in the event of power cut	72 hours
Porthole for installation of PT100/CO ₂ back up	Yes
Digital display	Yes
Data logger	Yes
RS 232 interface	Yes
RS 485 interface	Yes
USB up/down load	Yes
Defrost manual / auto	Manual
Castors	No
Chart recorder	Optional
Shelves (pcs)	1
Baskets (pcs)	No
Sub doors (pcs)	2
Lighting	No
Lock	Yes
Inner liner material	Stainless steel
Cabinet material	Varnished steel / stainless steel *
Colour (exterior)	White / stainless steel *
Refrigerant	R404a

* Optional, please contact us

We reserve the right to change specifications without notice and subject to errors.


Optional



1 The GSM alarm module sends a SMS message to one or several coded telephone numbers in case the temperature exceeds a fixed range.



2 SVS voltage stabilizers for excellent output voltage stability in case the voltage rises or drops.



3 Chart recorder for documentation of the temperature condition over a certain period of time.



4 CO₂ back up system ensures optimized safety.



5 Cryo gloves protect your hands and prevent frost bites when handling samples which are stored at down to -160 °C.



CO₂CARE



www.arctiko.com

www.co2care.eu